



ELEVATION

NOTES:

- BY-PASS MAY BE INSIDE METER BOX OR OUTSIDE METER BOX. IF INSTALLED OUTSIDE METER BOX A CASING AND COVER WILL BE REQUIRED OVER BY-PASS VALVE.
- 2. 1-1/2 INCH AND 2 INCH BY-PASS VALVES MUST BE BALL VALVES. THREE INCH AND LARGER TO BE RESILIENT SEATING SHUT-OFF VALVES.
- METERS DEEPER THAN 30 INCHES TO TOP OF PIPE MUST BE RAISED TO 30 INCHES.
- INLET AND OUTLET VALVES TO BE INSTALLED AT EACH END OF METER.
- 5. TEST TEE TO BE 3 PIPE DIAMETERS DOWNSTREAM OF METER.
- 6. WHEN CHARGING METER WITH WATER OPEN INLET VALVE VERY SLOWLY, THEN SLOWLY OPEN OUTLET VALVE.

MINIMUM VAULT SIZE

	Α	В	С
2",3"&4"	20"	48"	42"
4",6"&8"	40"	72"	42"
10"	60"	100"	42"

TURBINE METER SETTING WITH BY-PASS

REF. & REV.

AUG. 2002

CITY OF FRESNO

— 4 1